ISO 3745 电压(U): 200-240 [V] 目标: 电机类型: MGE80B f: 50/60 [Hz] P2: 0.55 [千瓦] n: 1450 - 2000 [转数/分钟] 测试条件: Load: No Load / Idle Sound test: 230 [V] f: 50 [Hz] 0 [千瓦] P2 · n: 750 [转数/分钟] 批注: 90 80 70 [dB(A)] 60 -by 50 40 29.0 30 24.7 22.4 22.8 20.0 18.5 20 10 0.8 1.0 -0.4 0 125 250 500 1k 8k Octave bands [Hz] Sound pressure level L_{pA} : 29.0 [dB(A)] L_{WA} : 41.5 [dB(A)] Sound power level References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871) 4871. (IEC 60064-9; Clause 8)

-Associated uncertainty K $_{WA}$ = 3 [dB(A)]

- "The sum of measured noise emission values and its associated uncertainty represents an upper boundary of the range of values which is likely to occur in measurements".

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

- "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2) at no-load. Generally, if ventilation noise is predominant the change may be

small; but, if the electromagnetic noise is predominant the change may be significant". - Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise

level may also occur on variable speed drives due to increased level of higher harmonics and potential coincidence between these and structural resonances.

 ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface. The emission sound pressure level obtained with this method represents the

average sound pressure level over the surface of area S in environmental

(IEC 60034-9 amd 1; Clause 7)

(IEC 60034; Clause 5.2)

(ISO 4871; Section B2)

(IEC 60034; Clause 5.2)

(ISO 11203; Clause 6.2.3)

ISO 3745 电压(U): 200-240 [V] 目标: 电机类型: MGE80B f: 50/60 [Hz] P2: 0.55 [千瓦] n: 1450 - 2000 [转数/分钟] 测试条件: Load: No Load / Idle Sound test: 230 [V] f: 50 [Hz] 0 [千瓦] P2 · n: 1125 [转数/分钟] 批注: 90 80 70 [dB(A)] 60 -by 50 40 34 0 29 9 29.3 30 23.6 23.5 20.0 20 7.2 10 4.9 1.7 0 125 250 500 1k 8k Octave bands [Hz] Sound pressure level L_{pA} : 34.0 [dB(A)] L_{WA} : 46.0 [dB(A)] Sound power level References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871) 4871. -Associated uncertainty K $_{WA}$ = 3 [dB(A)] (IEC 60064-9; Clause 8) - "The sum of measured noise emission values and its associated uncertainty (ISO 4871; Section B2)

represents an upper boundary of the range of values which is likely to occur in measurements".

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

(IEC 60034; Clause 5.2) - "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2)

at no-load. Generally, if ventilation noise is predominant the change may be small; but, if the electromagnetic noise is predominant the change may be significant".

- Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise level may also occur on variable speed drives due to increased level of higher harmonics and potential coincidence between these and structural resonances.

 ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the

(ISO 11203; Clause 6.2.3)

(IEC 60034; Clause 5.2)

(IEC 60034-9 amd 1; Clause 7)

ISO 3745 电压(U): 200-240 [V] 目标: 电机类型: MGE80B f: 50/60 [Hz] P2: 0.55 [千瓦] n: 1450 - 2000 [转数/分钟] 230 [V] 测试条件: Load: No Load / Idle Sound test: f: 50 [Hz] 0 [千瓦] P2 · n: 1500 [转数/分钟] 批注: 90 80 70 [dB(A)] 60 LpA 50 37.0 40 32.8 33.2 28.0 30 25.2 20.9 20 14.5 10.8 10 0.3 0 125 250 500 1k 8k Octave bands [Hz]

Sound pressure level L_{pA} : 37.0 [dB(A)]

 L_{WA} : 49.0 [dB(A)] Sound power level

ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO 4871.

-Associated uncertainty K $_{WA}$ = 3 [dB(A)]

- "The sum of measured noise emission values and its associated uncertainty represents an upper boundary of the range of values which is likely to occur in measurements".

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

- "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2)

significant". - Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise level may also occur on variable speed drives due to increased level of higher

at no-load. Generally, if ventilation noise is predominant the change may be small; but, if the electromagnetic noise is predominant the change may be

harmonics and potential coincidence between these and structural resonances. ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the

References:

(IEC 60034-9, ISO 3745 & 4871)

(IEC 60064-9; Clause 8)

(ISO 4871; Section B2)

(IEC 60034; Clause 5.2)

(IEC 60034-9 amd 1; Clause 7)

(IEC 60034; Clause 5.2)

(ISO 11203; Clause 6.2.3)

ISO 3745 电压(U): 200-240 [V] 目标: 电机类型: MGE80B f: 50/60 [Hz] P2: 0.55 [千瓦] n: 1450 - 2000 [转数/分钟] 测试条件: Load: No Load / Idle Sound test: 230 [V] f: 50 [Hz] 0 [千瓦] P2 · n: 1800 [转数/分钟] 批注: 90 80 70 [dB(A)] 60 LpA 50 40.0 38.1 40 32.8 30.5 27.5 30 22.6 18.8 20 10.4 10 2.8 0 125 250 500 8k Octave bands [Hz] Sound pressure level L_{pA} : 40.0 [dB(A)] L_{WA} : 52.0 [dB(A)] Sound power level References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871) 4871. -Associated uncertainty K $_{WA}$ = 3 [dB(A)] (IEC 60064-9; Clause 8) - "The sum of measured noise emission values and its associated uncertainty (ISO 4871; Section B2) represents an upper boundary of the range of values which is likely to occur in

measurements".

at no-load. Generally, if ventilation noise is predominant the change may be

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

- "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2)

small; but, if the electromagnetic noise is predominant the change may be significant". - Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise level may also occur on variable speed drives due to increased level of higher

harmonics and potential coincidence between these and structural resonances.

 ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the

(ISO 11203; Clause 6.2.3)

(IEC 60034; Clause 5.2)

(IEC 60034-9 amd 1; Clause 7)

(IEC 60034; Clause 5.2)

ISO 3745 电压(U): 200-240 [V] 目标: 电机类型: MGE80B f: 50/60 [Hz] P2: 0.55 [千瓦] n: 1450 - 2000 [转数/分钟] 测试条件: Load: No Load / Idle Sound test: 230 [V] f: 50 [Hz] 0 [千瓦] P2 · n: 2000 [转数/分钟] 批注: 90 80 70 [dB(A)] 60 LpA 50 42.5 40.0 36.8 40 33.7 29.0 30 23.4 21.2 20 12.0 10 0.8 0 125 250 500 1k 8k Octave bands [Hz] Sound pressure level L_{pA} : 42.5 [dB(A)] L_{WA} : 54.5 [dB(A)] Sound power level References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871)

4871.

-Associated uncertainty K $_{WA}$ = 3 [dB(A)]

- "The sum of measured noise emission values and its associated uncertainty represents an upper boundary of the range of values which is likely to occur in measurements".

at no-load. Generally, if ventilation noise is predominant the change may be

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

- "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2)

small; but, if the electromagnetic noise is predominant the change may be significant". - Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise level may also occur on variable speed drives due to increased level of higher

harmonics and potential coincidence between these and structural resonances. ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the

(IEC 60034; Clause 5.2)

(IEC 60034-9 amd 1; Clause 7)

(IEC 60064-9; Clause 8)

(ISO 4871; Section B2)

(IEC 60034; Clause 5.2)

(ISO 11203; Clause 6.2.3)