ISO 3745 电压(U): 目标: 电机类型: MGE112MC 3 x 380-500 [V] f: 50/60 [Hz] P2: 4 [千瓦] n: 2900-4000 [转数/分钟] 测试条件: Load: No Load / Idle Sound test: 400 [V] f: 50 [Hz] 0 [千瓦] P2 · n: 1500 [转数/分钟] 批注: 90 80 70 [dB(A)] 60 LpA 50 44.5 39.3 38.9 38.5 40 32.6 26.7 26.5 30 17.3 20 10 5.5 0 63 125 250 500 1k 8k Octave bands [Hz] Sound pressure level L_{pA} : 44.5 [dB(A)] Sound power level L_{WA} : 56.5 [dB(A)] References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871) 4871. -Associated uncertainty K $_{WA}$ = 3 [dB(A)] (IEC 60064-9; Clause 8) - "The sum of measured noise emission values and its associated uncertainty (ISO 4871; Section B2) represents an upper boundary of the range of values which is likely to occur in measurements".

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9. - "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2) at no-load. Generally, if ventilation noise is predominant the change may be

(IEC 60034; Clause 5.2)

small; but, if the electromagnetic noise is predominant the change may be significant". - Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise

level may also occur on variable speed drives due to increased level of higher

(IEC 60034-9 amd 1; Clause 7)

harmonics and potential coincidence between these and structural resonances. ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the

(IEC 60034; Clause 5.2)

sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

(ISO 11203; Clause 6.2.3)

1.50	3745
130	3/45


电机类型: MGE112MC 电压(U): 3 x 380-500 [V] f: 50/60 [Hz]

P2: 4 [千瓦] n: 2900-4000 [转数/分钟]

测试条件: Load: No Load / Idle Sound test: 400 [V]

f: 50 [Hz] 0 [千瓦] P2: n: 2250 [转数/分钟]

批注:



Sound pressure level L_{pA} : 53.5 [dB(A)]

 L_{WA} : 66.0 [dB(A)] Sound power level

ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871) 4871.

-Associated uncertainty K $_{WA}$ = 3 [dB(A)]

- "The sum of measured noise emission values and its associated uncertainty represents an upper boundary of the range of values which is likely to occur in measurements".

(IEC 60034; Clause 5.2)

(IEC 60064-9; Clause 8)

(ISO 4871; Section B2)

References:

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9. - "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2) at no-load. Generally, if ventilation noise is predominant the change may be

small; but, if the electromagnetic noise is predominant the change may be significant".

(IEC 60034-9 amd 1; Clause 7)

- Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise level may also occur on variable speed drives due to increased level of higher harmonics and potential coincidence between these and structural resonances.

(IEC 60034; Clause 5.2)

 ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the (ISO 11203; Clause 6.2.3)

ISO 3745


电压(U): 目标: 电机类型: MGE112MC 3 x 380-500 [V] f: 50/60 [Hz]

P2: 4 [千瓦] n: 2900-4000 [转数/分钟]

测试条件: Load: No Load / Idle Sound test: 400 [V]

f: 50 [Hz] 0 [千瓦] P2 · n: 3000 [转数/分钟]

批注:



Sound pressure level L_{pA} : 61.0 [dB(A)]

Sound power level L_{WA} : 73.5 [dB(A)]

ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO 4871.

(IEC 60034-9, ISO 3745 & 4871) (IEC 60064-9; Clause 8)

References:

-Associated uncertainty K $_{WA}$ = 3 [dB(A)]

- "The sum of measured noise emission values and its associated uncertainty (ISO 4871; Section B2) represents an upper boundary of the range of values which is likely to occur in

measurements".

(IEC 60034; Clause 5.2)

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9. - "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2) at no-load. Generally, if ventilation noise is predominant the change may be

small; but, if the electromagnetic noise is predominant the change may be significant".

(IEC 60034-9 amd 1; Clause 7)

- Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise level may also occur on variable speed drives due to increased level of higher harmonics and potential coincidence between these and structural resonances.

(IEC 60034; Clause 5.2)

 ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the (ISO 11203; Clause 6.2.3)

ISO 3745


电压(U): 目标: 电机类型: MGE112MC 3 x 380-500 [V] f: 50/60 [Hz]

P2: 4 [千瓦] n: 2900-4000 [转数/分钟]

400 [V] 测试条件: Load: No Load / Idle Sound test:

f: 50 [Hz] 0 [千瓦] P2 · n: 3600 [转数/分钟]

批注:



Sound pressure level L_{pA} : 65.5 [dB(A)]

Sound power level L_{WA} : 78.0 [dB(A)]

References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871) 4871.

- -Associated uncertainty K $_{WA}$ = 3 [dB(A)]
- "The sum of measured noise emission values and its associated uncertainty represents an upper boundary of the range of values which is likely to occur in measurements".

•Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

(IEC 60034; Clause 5.2)

(IEC 60064-9; Clause 8)

(ISO 4871; Section B2)

- "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2) at no-load. Generally, if ventilation noise is predominant the change may be

small; but, if the electromagnetic noise is predominant the change may be significant". - Additionally - as outlined in IEC 60034-9 Amendment 1 - an increase in the noise

level may also occur on variable speed drives due to increased level of higher

(IEC 60034-9 amd 1; Clause 7)

harmonics and potential coincidence between these and structural resonances. ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the

(IEC 60034; Clause 5.2)

sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the

(ISO 11203; Clause 6.2.3)

ISO 3745


电压(U): 电机类型: MGE112MC 3 x 380-500 [V] f: 50/60 [Hz]

P2: 4 [千瓦] n: 2900-4000 [转数/分钟]

400 [V] 测试条件: Load: No Load / Idle Sound test:

f: 50 [Hz] 0 [千瓦] P2 · n: 4000 [转数/分钟]

批注:



Sound pressure level L_{pA} : 68.5 [dB(A)]

 L_{WA} : 80.5 [dB(A)] Sound power level

4871.

References: ulletSound power values L $_{W\ A}$ determined according to IEC 60034-9, ISO 3745 and ISO (IEC 60034-9, ISO 3745 & 4871)

-Associated uncertainty K $_{WA}$ = 3 [dB(A)]

- "The sum of measured noise emission values and its associated uncertainty represents an upper boundary of the range of values which is likely to occur in measurements".

(IEC 60034; Clause 5.2) •Sound power evaluated at rated speed and no load as specified in IEC 60034-9.

- "The sound power levels, under full load condition, are normally higher than those (IEC 60034-9; Clause 6, Note 2) at no-load. Generally, if ventilation noise is predominant the change may be small; but, if the electromagnetic noise is predominant the change may be significant".
- Additionally as outlined in IEC 60034-9 Amendment 1 an increase in the noise level may also occur on variable speed drives due to increased level of higher harmonics and potential coincidence between these and structural resonances.

(IEC 60034; Clause 5.2) ullet The equivalent sound pressure level L $_{
m pA}$ at 1 m distance are determined from the sound power level via ISO 11203 method Q2

- The observer surface area S is given by a box shape enveloping the source and here calculated for a specified distance of 1 m between the source and the observer surface.

The emission sound pressure level obtained with this method represents the (ISO 11203; Clause 6.2.3)

average sound pressure level over the surface of area S in environmental

(IEC 60064-9; Clause 8)

(ISO 4871; Section B2)

(IEC 60034-9 amd 1; Clause 7)